



# POLE CAMERA

This versatile all-in-one unit delivers exceptional coverage within a sleek, compact enclosure designed for versatile mounting options. Employ a pole camera to actively monitor and deter potential intruders or safeguard against unauthorized removal of tools, equipment, or materials by employees at any site.

A pivotal addition to your temporary surveillance setup, pole cameras are available in various camera configurations, ensuring precise and comprehensive site coverage. Each unit can easily be powered via a standard 120v supply or can be conveniently configured to run off solar energy.



## REMOTE SITE MANAGEMENT

View your site live, 24/7, from any location, on any device.



## PERIMETER WATCH

Monitor specific areas of concern while maintaining a full field of view.



## SITE SECURITY

Live, 24/7, US based, monitoring services available. Alerts sent to you and/or your local law enforcement of suspicious activities.



## STORED FOOTAGE

Each camera saves up to 14 days of rolling footage to conveniently access events that are not caught right away.



## PTZ CAMERAS

Pan, tilt, and zoom cameras allow for remote camera repositioning when cameras need to be relocated.



## SPECIFICATIONS

- 120V Power Supply
- Cellular 4G LTE router
- Optional solar charge
- Mounting bracket: 3/8" holes or 1/2" strap
- Optional talk down speaker
- Onboard redundant hard drive
- Lockable control housing
- Voltage regulator
- Loss of power alarm: 5 Ah
- 1 x Nanoflar Strobe

## PTZ CAMERA SPECIFICATION

- 2 x 2-megapixel 1920 x 1080 (PTZ)
- 25 x Optical Zoom
- 16 x Digital Zoom
- Up to 475' IR distance
- NDAA Compliant

## ADDITIONAL CAMERA CONFIGURATIONS

- 2 x 5-megapixel 2592 x 1944 (Fixed)
- 1 x 8-megapixel 3840 x 2160 (Fisheye)



## DIMENSIONS:

- Length: 40"
- Width: 17"
- Height: 10"
- Weight: 32 lbs.

**AVC-PHN21X25LW**  
2MP 25X NETWORK IR SPEED DOME CAMERA



## 2MP NETWORK IR SPEED DOME CAMERA

*2MP 25x IR NETWORK SPEED DOME, 12V&PoE*

The AVC-PHN21X25LW camera is a 2MP Network Camera using Infinite-Star™ technology, with an ultra-low lux sensitivity, providing crisp color images of the environment even at night. Featuring powerful optical zoom and accurate pan/tilt/zoom performance, the camera provides a wide monitoring range and great detail. The camera delivers 2MP full high definition resolution at 25/30fps. The camera is equipped with smooth control, high quality image, and good protection, meeting compact size demands of video surveillance applications.

## FUNCTIONS

- 1/2.8" Progressive Scan CMOS
- Up to 1920 x 1080 Resolution
- Min. illumination: Color: 0.005 Lux@(F1.6, AGC ON) / B/W: 0.001 Lux@(F1.6, AGC ON) / 0 Lux with IR
- 25x Optical Zoom, 16x Digital Zoom
- 120 dB WDR, 3D DNR, Smart IR
- Up to 150m IR distance
- Smart H.265/H.264 video compression
- IP66, -30°C~55°C, ADC12 + PC/GF
- PoE+ (802.3.at, class 3) and DC12V
- ONVIF, API and SDK
- NDAA Compliant
- Includes wall mount (AVM-PT-WMT-N20)

## DIMENSIONS

Unit: inch (mm)

