



SOLAR SURVEILLANCE TRAILER

Caprock's flagship Solar Surveillance Trailer stands as the pinnacle of innovation in surveillance technology. Representing our dedication to cutting-edge solutions, this solar-powered unit redefines site security with unmatched features. With a self-sustained power source, widest field of view, and a comprehensive array of functionalities, it sets a new standard for monitoring solutions, ensuring unparalleled site security and surveillance excellence.



REMOTE SITE MANAGEMENT

View your site live, 24/7, from any location, on any device.



ENHANCED SAFETY FEATURES

Made to meet job site safety practices each unit offers an Isolated and lockable electrical cabinet, lockable mast, outriggers, fire extinguisher and wheel chocks.



SITE SECURITY

Live, 24/7, US based, monitoring services available. Alerts sent to you and/or your local law enforcement of suspicious activities.



LOCAL NVR FOOTAGE

A local NVR allows instant access up to a 30 day rolling average of footage from the system cabinet.



PTZ CAMERAS

Pant, tilt, and zoom cameras allow for remote camera repositioning when cameras need to be relocated.



TRAILER SPECIFICATIONS

- 4 x 2MP PTZ cameras w/ 30x zoom
- 1 x 1080P Fixed Eyeball
- 1,380W solar array
- 2000 Ah of AGM batteries
- Optional backup generator
- 25' mast height
- Cellular 4G LTE router
- Talk down speaker
- Onboard redundant hard drive
- Backup 120V AC battery charger

PTZ CAMERA SPECIFICATION

- 2 x 2-megapixel 1920 x 1080 (PTZ)
- 25 x Optical Zoom, 16 x Digital Zoom
- Up to 475' IR distance
- NDAA Compliant



STOWED DIMENSIONS:

- Length: 15'
- Width: 7'
- Height: 10'
- Weight: 4,500 lbs.

DEPLOYED DIMENSIONS:

- Length: 15'
- Width: 12'
- Height: 25'
- Weight: 4,500 lbs.

AVC-PHN21X25LW
2MP 25X NETWORK IR SPEED DOME CAMERA



2MP NETWORK IR SPEED DOME CAMERA

2MP 25x IR NETWORK SPEED DOME, 12V&PoE

The AVC-PHN21X25LW camera is a 2MP Network Camera using Infinite-Star™ technology, with an ultra-low lux sensitivity, providing crisp color images of the environment even at night. Featuring powerful optical zoom and accurate pan/tilt/zoom performance, the camera provides a wide monitoring range and great detail. The camera delivers 2MP full high definition resolution at 25/30fps. The camera is equipped with smooth control, high quality image, and good protection, meeting compact size demands of video surveillance applications.

FUNCTIONS

- 1/2.8" Progressive Scan CMOS
- Up to 1920 x 1080 Resolution
- Min. illumination: Color: 0.005 Lux@(F1.6, AGC ON) / B/W: 0.001 Lux@(F1.6, AGC ON) / 0 Lux with IR
- 25x Optical Zoom, 16x Digital Zoom
- 120 dB WDR, 3D DNR, Smart IR
- Up to 150m IR distance
- Smart H.265/H.264 video compression
- IP66, -30°C~55°C, ADC12 + PC/GF
- PoE+ (802.3.at, class 3) and DC12V
- ONVIF, API and SDK
- NDAA Compliant
- Includes wall mount (AVM-PT-WMT-N20)

DIMENSIONS

Unit: inch (mm)

