



ELECTRIC SURVEILLANCE CUBE

Use a forklift to move this temporary surveillance system around your job site. This all-in-one unit comes with (4) 2-megapixel cameras providing excellent coverage. Its semi-large footprint is a deterrent to potential intruders and prevents employees from taking tools, equipment, or materials from the site. Each unit requires a 120v power supply and has a backup battery bank.



REMOTE SITE MANAGEMENT

View your site live from any location, on any device.



TALK DOWN SPEAKER

Communicate directly through a mobile app, while our monitoring station can also use them to deter intruders in real-time.



PERIMETER WATCH

Monitor specific areas of concern while maintaining a full-field of view.



LIVE VIDEO MONITORING

Live, 24/7, US based, monitoring services available. Alerts sent to you and/or your local law enforcement of suspicious activities.



MOBILE

Designed for effortless mobility, this compact trailer moves easily between locations without the need for specialized transport or setup.



PTZ CAMERAS

Pant, tilt, and zoom cameras allow remote camera repositioning when cameras need to be relocated.



SPECIFICATIONS

- 4 x 2MP PTZ cameras w/ 20x zoom
- 750 Ah of AGM batteries
- Forklift accessible
- 25' mast height
- Cellular 4G LTE router
- Talk down speaker
- Onboard redundant hard drive
- Lockable control housing
- Backup 120V AC battery charger
- Voltage regulator
- Thermostatically controlled cooling fan

PTZ CAMERA SPECIFICATION

- 4-megapixel
- 25 x Optical Zoom
- 16 x Digital Zoom
- Up to 475' IR Distance
- NDAA Compliant



**STOWED
DIMENSIONS:**

- Length: 4'
- Width: 5'
- Height: 24'6"
- Weight: 2,200 lbs.

**DEPLOYED
DIMENSIONS:**

- Length: 4'
- Width: 5'
- Height: 8'
- Weight: 2,200 lbs.



AVC-PNN41X25LW

NDAA COMPLIANT | CE | FC

4MP NETWORK IR SPEED DOME CAMERA

OVERVIEW

- High Efficiency Video Coding (H.265)
- 1/2.7" 4MP Progressive Scan CMOS
- Up to 2560 x 1440 @30fps Resolution
- Min. illumination: Color: 0.01 Lux@ (F1 .65, AGC ON)/
- B/W: 0.002 Lux@ (F1 .65, AGC ON)/ 0 Lux with IR
- 25x Optical Zoom
- WDR, HLC, BLC, 3D DNR, Defog
- Up to 150m smart IR distance
- PoE (802.3 at class 4)
- IP66
- Support H.265+/H.265 Video Compression
- Superior Image Quality
- Working Environment and Interoperability
- NDAA Compliant
- Includes wall mount (AVM-PT-WMT-N20)
- Built-in micro SD card slot with video and still image capture function (up to 256GB)

DIMENSIONS

Unit : inch(mm)

