



POLE CAMERA 2-CAMERA

This versatile all-in-one unit delivers exceptional coverage within a sleek, compact enclosure designed for versatile mounting options. Employ a pole camera to actively monitor and deter potential intruders or safeguard against unauthorized removal of tools, equipment, or materials by employees at any site.

A pivotal addition to your temporary surveillance setup, pole cameras are available in various camera configurations, ensuring precise and comprehensive site coverage. Each unit can easily be powered via a standard 120v supply or can be conveniently configured to run off solar energy.



REMOTE SITE MANAGEMENT

View your site live, 24/7, from any location, on any device.



TALK DOWN SPEAKER

Communicate directly through a mobile app, while our monitoring station can also use them to deter intruders in real-time



LIVE VIDEO MONITORING

Live, 24/7, US based, monitoring services available. Alerts sent to you and/or your local law enforcement of suspicious activities.



STORED FOOTAGE

Each camera saves up to 14 days of rolling footage to conveniently access events that are not caught right away.



PTZ CAMERAS

Pant, tilt, and zoom cameras allow for remote camera repositioning when cameras need to be relocated.



SPECIFICATIONS

- 120V Power Supply
- Cellular 4G LTE router
- Optional solar charge
- Mounting bracket: 3/8" holes or 1/2" strap
- Optional talk down speaker
- Onboard redundant hard drive
- Lockable control housing
- Voltage regulator
- Loss of power alarm: 5 Ah
- 1 x Nanoflar Strobe

PTZ CAMERA SPECIFICATION

- 2 x 2-megapixel
- 25 x Optical Zoom
- 16 x Digital Zoom
- Up to 475' IR distance
- NDAA Compliant

ADDITIONAL CAMERA CONFIGURATIONS

- 5 -megapixel 2592 x 1944 (Fixed)
- 8-megapixel 3840 x 2160 (Fisheye)
- Consultation available for custom options



DIMENSIONS:

- Length: 40"
- Width: 17"
- Height: 10"
- Weight: 32 lbs.

AVC-PHN21X25LW
2MP 25X NETWORK IR SPEED DOME CAMERA



AVC-PNN41X25LW

NDAA
Compliant | CE | FCC

4MP NETWORK IR SPEED DOME CAMERA

OVERVIEW

- High Efficiency Video Coding (H.265)
- 1/2.7" 4MP Progressive Scan CMOS
- Up to 2560 x 1440 @30fps Resolution
- Min. illumination: Color: 0.01 Lux@ (F1 .65, AGC ON)/
- B/W: 0.002 Lux@ (F1 .65, AGC ON)/ 0 Lux with IR
- 25x Optical Zoom
- WDR, HLC, BLC, 3D DNR, Defog
- Up to 150m smart IR distance
- PoE (802.3 at class 4)
- IP66
- Support H.265+/H.265 Video Compression
- Superior Image Quality
- Working Environment and Interoperability
- NDAA Compliant
- Includes wall mount (AVM-PT-WMT-N20)
- Built-in micro SD card slot with video and still image capture function (up to 256GB)

DIMENSIONS

Unit : inch(mm)

